



**+255 22 2135834**

[info@plvdigital.co.tz](mailto:info@plvdigital.co.tz)





## Specification

- High strength ABS cover casing.
- Stainless steel heating element.
- **Mini size, compact design, convenient for installation.**
- Direct temperature setting, automatic thermostat, automatic memory function avoid repeated operation.
- Touch screen for operation, LED digital display show the working condition, setting temperature and outlet temperature.
- Electricity leakage protection, anti-scalding protection, over-pressure and overheat protection. Water and electricity isolation protection
- Fault auto-detection technique, the cause will be displayed automatically with failure.

## Technology Data

<b>Model</b>	TZXFJ50FSG
<b>Phase</b>	1
<b>Rated Voltage</b>	220-240V
<b>Rated Power</b>	5kW
<b>Rated Current</b>	21.7A
<b>Rated Pressure</b>	0.02-0.6MPa
<b>Safety class</b>	IP25
<b>Connecting wires section</b>	
<b>Temp. setting arrange</b>	30-55° C
<b>Min. Water flow to activate unit</b>	1.5L/min
<b>Overheat protection</b>	65° C
<b>Thermal cut-off</b>	95° C
<b>Pipe section</b>	G1/2"
<b>Product Size</b>	396*220*88mm

CB CE ErP Ready

